ARM 36.22.307, 601, 605 1003, 1004, 1011, 1013 1103, 1222, 1240, 1301 1306, 1309, and 1417

Submit In Quadruplicate To:

MONTANA BOARD OF OIL AND GAS CONSERVATION RECEIVED 2535 ST. JOHNS AVENUE **BILLINGS, MONTANA 59102**


JAN 1 0 2018

S	UNDRY NOTICE	SAND	REPO	RT OF WELLS MONTANA BOARD OF OIL 8	S _L		
Operator Denbury Onshore, Ll	-c			Lease Name: GAS CONSERVATION - BILLIA S&H Rentals	1000		
Address 5320 Legacy Drive			Lease Type (Private/State/Federal):	\dashv			
City Plano State	TX Zip Code	75024		Private			
Telephone Number (972) 673-2000 Fax Number ()				Well Number: 23X-08			
Location of Well (1/4-1/4 section and	footage measuremen	ts):		Unit Agreement Name;			
NE-SW 1606' FSL & 2160' FWL, S	Section 8, T14N-R55E						
				Field Name or Wildcat:			
				Glendive Field			
If directionally or horizontally drilled, sho	w both surface and botto	m hole loo	cations)	Section, Township, and Range:			
API Number:	Well Type (oil, gas	, injectior	n, other):	Sec 8, T14N - R55E			
25 021 21121 State County Well	Oi	iI		County: Dawson County, MT			
Indicate below with an X the nature of	of this notice, report, or	other da	ıta:				
Notice of Intention to Change plans			Subseque	ent Report of Mechanical Integrity Test			
Notice of Intention to Run Mechanica	I Integrity Test	(X)	Subseque	Subsequent Report of Stimulation or Chemical Treatment			
Notice of Intention to Stimulate or to	Chemically Treat	(X)	Subseque	Subsequent Report of Perforation or Cementing			
Notice of Intention to Perforate or to	Cement	X	Subseque	Subsequent Report of Well Abandonment			
Notice of Intention to Abandon Well			-	ubsequent Report of Pulled or Altered Casing			
Notice of Intention to Pull or Alter Ca	sing		-	Subsequent Report of Drilling Waste Disposal			
Notice of Intention to Change Well S	tatus	X	Subsequent Report of Production Waste Disposal				
Supplemental Well History			Subsequent Report of Change in Well Status				
_	lt Water Disposal	_ 💌	Subsequent Report of Gas Analysis (ARM 36.22.1222)				
		_ 🖂 🗀 📗					
	Describe Propos	ed or Co	mpleted (Operations:			
				ration diagrams, analyses, or other information a completion date for completed operations.	as		
Denbury requests approval to con	vert the subject well	ore fron	n Produce	r to SWD in the Mission Canyon-Lodgepole			
	•			Public Notice has been submitted to the Gle	ndive		
Ranger Review and Helena Indepe							
BOARD USI	E ONLY		The up	dersigned hereby certifies that the information cont	ained		
				application is true and correct:	J. 100		
Approved	_			Whi. 11/11.			
Date			1/	/8/2018 / White			
				Date Signed (Agent)			
			Naomi	Johnson - Regulatory Compliance Specialist			
Name	Title			Print Name & Title			

SUPPLEMENTAL INFORMATION

NOTE: Additional information or attachments may be required by Rule or by special request.

Plot the location of the well or site that is the subject of this notice or report.



AD	D I	ICE	ONI	v
 AK	1) L	126	UNI	- 7

CONDITIONS OF APPROVAL

The operator must comply with the following condition(s) of approval:

Failure to comply with the conditions of approval may void this permit.



Convert to SWD Procedure

S&H Rentals #23X-8

API#: 2502121121, Sec 8 - T14N - R55E

Dawson County, MONTANA


OBJECTIVE OF OPERATION:


- TA Red River
- Complete as Mission Canyon Salt Water Disposal



Procedure:

- 1. NOTE: Check local Well File before beginning job. Check location and anchors.
- 2. MIRU workover rig. Check well pressures. Remove horses head.
- 3. POOH and LD rods and pump.
- 4. NU BOP. Test BOPs as per Denbury standards.
- 5. Release anchor, POOH and lay down 2-7/8" tubing.
- 6. PU bit and scrapper, Clean out to PBTD of ±8,870'. Circulate hole clean, TOOH.
- 7. TIH w/CICR on workstring, set CICR @8742' (30' above top perf). Establish injection rate and pressure. If perforations are plugged off alter the next step to spotting 200' balanced plug to isolate the Red River. Test csq to 800# (report any leaks and remediate)
- 8. MIRU Cementing Unit. Lay and test lines. Mix and pump 100 sx of cement to squeeze the Red River Interval. Sting out of retainer and leave 5 sx on top of CICR. Circulate hole clean. TOOH 5 stands. WOC. RDMO Cementers.
- 9. TIH to tag cement before TOOH.
- 10. MIRU Wireline to perforate Mission Canyon from 7574'-7650' (76' total) at 4 spf, 90° Phasing (charges/exact perf depths TBD).
- 11. RIH with test packer and workstring. Set packer @ ±7534' and establish injection rate. Stimulate well if necessary with acid and bio balls. Flow back load if well will flow.
- 12. POOH and lay down packer and work string.
- 13. PU retrievable packer and 2-7/8" coated tubing (IPC) with packer @ ±7,534'. Hydro test tubing while TIH.
- 14. Circulate packer fluid. Set packer @+/-7,534'. Land tubing, ND BOP, NU Wellhead. Pressure test to 800#.
- 15. RD MO WO rig. Clean location.
- 16. MIT well once permit is issued.
- 17. Put well on injection once state has approved.





MONTANA BOARD OF OIL AND GAS CONSERVATION UNDERGROUND INJECTION CONTROL PERMIT APPLICATION

Denbury Onshore, LLC Well No. S&H Rentals 13X-08 Glendive Field Section , T14N-R55E Dawson, Montana

Area of Review

The area of review (AOR) is a fixed radius of ¼ mile from the well bore of the subject well. The area of review is shown on the attached map.

Notification of Surface Owner(s)

Surface owners holding properties within the prescribed AOR were notified of Denbury's intent to apply for a permit to commence water injection into the subject well bore. Notification by registered mail was sent to the following surface owner(s):

Trangmoe Land LLP 115 Cooke St. Glendive, MT 59330-2016

Dale Schendel and Wendi L. Trustees 6038 Glass Dr. Helena, MT 59602-6454

Attached is a copy of the letters sent to surface owners, giving notice of our intent to apply for this injection permit.

Public Notification

Notice of intent to apply for a permit to inject water into the subject well has also been posted in the following newspapers for public inspection.

Helena Independent Record Attn: Billie Jo Williams P.O. Box 4249 Helena, Montana 59604-4249

Glendive Ranger Review Attn: Elizabeth Kaiser P.O. Box 61 Glendive, Montana 59330 Also attached is a copy of the legal notice submitted to the newspapers which provided the public with knowledge of our intent to apply for an injection permit.

Fresh Water Sources (Surface & USDW) within the AOR

There is one fresh water well located within a ½ mile radius of the subject well. A search of the Montana Ground Water Information Center database identified the well as GWIC 702167. See attachment.

No known surface or underground sources of drinking water will be affected by salt water injection into the subject well.

Existing Well Bores within the AOR

There is one wellbore that falls within the ¼ mile radius of the S&H Rentals 23X-08. A down hole schematic for this well bore is attached.

The Larson 24-8 (25-021-05227) is an active SWD well.

Corrective Action Proposal

No corrective action is deemed necessary for the subject well or other existing wells contained within the ¼ mile AOR.

Formation Tops

Formation	MD (ft)*
Greenhorn	2760'
Dakota	3693'
Spearfish	5227'
Minnekahta Limestone	5534'
Heath	5991'
Kibby Limestone	6616'
Ratcliffe	7065'
Mission Canyon	7134'
Lodgepole	7806'
Siluro-Ordovician	8260'
Stony Mountain	8575'
Red River	8722'

^{*}KB Elevation 2105'

Injection Pressures (Minnelusa)

Surface fracture Pressure = [Fracture Gradient x Depth to Perforations] –

[S.G. of Injected Fluids x 0.433 psi/ft x Depth to
Perforations] + Tubing Friction (assumed Negligible)

Depth to top perforation = 7134'

S.G. of Injection Fluid = Approximately 1.020 (see representative water analysis)

Fracture Gradient = Approximately 0.8 psi/ft

Operating Data

Actual operating conditions will be limited to a pressure not exceeding fracture pressure or pressure that causes fluid to go out of zone. Based on attached calculations, we request a permit for a limiting surface pressure of 2556 psi, the fracture pressure at the Mission Canyon top perforation.

The annular space between the tubing and casing will be filled with fresh water treated with a corrosion inhibitor, a scale inhibitor and an oxygen scavenger as outlined in the construction procedures.

Injected fluids into the subject well will be field salt-water from the Glendive Unit. A representative analysis of the injectate is attached.


Conversion Procedures

The S&H Rentals 23X-08 is currently a shut-in producer in the Red River formation. Denbury desires approval to perform conversion operations on the subject well in advance of salt water disposal approval. Work on the well would proceed, however injection would not commence until official approval is received from the Board. Contract personnel, working according to Denbury's plan, specifications, and safety practices may be employed to perform some or all of the actual onsite conversion operations.

Aquifer Exemption


An Aquifer Exemption will not be required.


S&H Rentals 23X-08 - Mission Canyon-Lodgpole SWD




23X-08

Twn 14N Rge 55E Sec 8 25021211210000







De

Denleve

LOCATE WELL CORRECTLY

(SUBMIT IN TRIPLICATE)

TO

OIL AND GAS CONSERVATION COMMISSION OF THE STATE OF MONTANA BILLINGS OR SHELBY

LOG OF WELL

	5788	93034	7	Form	No. 4
18	SCI A	e de	New New	200.3	6 23 1)
n	1404	2148	DU		
27.52	REC	E 1 V S S CONS. O TE OF MO TE LENA	Mi* C	20	
180	OIL STI	HELENA	10	7	
1	£4191	SIFIE	15/1		

Company_	1700	1 Oil Co Broadwa	mpany		ease	arson		w	ell No. 24-8
Address					Field	(or Area	()G1	endive Field	
Pha mall ia			(M)			(TE)			
i ne well is	located ooc	It. Iron	n (S) line and	1900	ft. fron	(W) lin	e of Sec	8	
									2090 GL, 2102 (D.F., R.B. or G.L.)
Commence	d drilling		August	19 , 19	966 ; Com	pleted		November	7 19.66
I me wen	as oil we	ite.			Signed_	8	732	Decie	is for the condition
					Title	Divis	ion Expl	oitation Eng	ineer
					Date	Novem	ber 21,	1966	8 1
rom 8/	430 to		oil by O, gas	s by G, w		8772 8812 8890	rmation if	known) 790½ - 0 817 - 0 920 - 0	
				CASIN	G RECOR	D	LAL,		
Size Casing	Weight Per Ft.	Grade	Thread	Casing	Set	From	То	Sacks of Cement	Cut and Pulled from
3-5/8"	24#			1023	3	0	1023	365	0
5-1/2"	14,15.5&17#	J-55 & P-110	ST&C<&C	8938	3	0	8938	560	0
152		12.110							
	,		The state of the s	TUBIN	G RECOR	D	1.6	REC	EIVED
	Size Tubir	ng -1	Weight Per Ft	Grade	Thread	Ame	ount	Perforations NOV	
able tools	s were used from					t	oTD	OF THE STATE OF	ONIJJID - AKATHCZI 1
otal depth	8938 ft.	; Plugged	back to	8820	T.D.; O	pen hole	from	to	
	PERFORA	TIONS				IDIZED, SH	OT, SAND FR	ACED, CEMENTED	
From	From To Size and Type			From	nterval To		Amount of Material Used		Pressure
As	per attach	ment				As per	attachm	ent	
					PRODUCI	ION	P&A show p	lugs above)	
'all is pro	MILCIDO SECUE		ALVA AND T	•	(pool) .	ormanion.			
_				~1		20100000000000000000000000000000000000	20		
ell is pro			per	24 h	ours	pumping	wing)		·
_	120 bs	arrels of oil	er 24	hou	(pur	pumping	wing)		n

INITIAL	PRODUCTION-	-(Continued

Initial 10-day average production	(bbl./day) (if taken)	
Pressures (if measured): Tubing	psi flowing;	psi shut-in
Gravity 37.4 API (corrected	psi flowing;	psi shut-in

DRILL STEM TESTS

D.S.T. No.	From	То	Tool Open (Min.)	Shut-In	F.P.	S.L.P.	Recovery	Cushion
	บ . ฮม	5-020-5				บ	, on epito, and	
					None			
					C			

LOGS ŔUN

Type -		vals
	From	To
BHC-Sonic, GR, LL-3, MLL; Section		
Gauge and NML failed		

From	To	FORMATIC SAMPLE AND COR	ON RECORD		Top of Formation
10 m	LC I	- N	J.) (-) (-	
ie:			فتنادر مدامه	T T	
			ŢĔĘ <mark>O</mark> ŢŌĿ	un Total Voluto.	
	ur	T.		e wā	
		duise Je	;		٠
	17				A 2 3 %
	ا دانند نازر	I ((6.4)	John Maria Ra	4.
	100		<u>_</u> #1280.		U/=
	* 53		. 21		-
				a e	
, λ					
	1 1		2	× >,	•

MONTANA WELL LOG REPORT

Plot this site in State Library Digital Atlas Plot this site in Google Maps View field visits for this site

Other Options

Return to menu

This well log reports the activities of a licensed Montana well driller, serves as the official record of work done within the borehole and casing, and describes the amount of water encountered. This report is compiled electronically from the contents of the Ground Water Information Center (GWIC) database for this site. Acquiring water rights is the well owner's responsibility and is NOT accomplished by the filing of this report.

Site Name: **GWIC Id: 702167**

Section 1: Well Owner(s)

Section 2: Location

Township Range Section **Quarter Sections** 14N 55E NE1/4 SE1/4 SE1/4 County Geocode

DAWSON Latitude Longitude Geomethod **Datum** 46.9736 -104.8055 UNKNOWN NAD27 **Ground Surface Method Ground Surface Altitude** Datum Date

2134

Addition **Block** Lot

Section 3: Proposed Use of Water

STOCKWATER (1)

Section 4: Type of Work Drilling Method: BORED

Status: NEW WELL

Section 5: Well Completion Date

Date well completed: Monday, January 01, 1951

Section 6: Well Construction Details

There are no borehole dimensions assigned to this well. There are no casing strings assigned to this well. There are no completion records assigned to this well.

Annular Space (Seal/Grout/Packer)

There are no annular space records assigned to this well.

Section 7: Well Test Data

Total Depth: 13 Static Water Level: Water Temperature:

Unknown Test Method *

Yield _ gpm.

Pumping water level feet. Time of recovery _ hours. Recovery water level feet.

* During the well test the discharge rate shall be as uniform as possible. This rate may or may not be the sustainable yield of the well. Sustainable yield does not include the reservoir of the well casing.

Section 8: Remarks

Section 9: Well Log **Geologic Source** Unassigned

Lithology Data

There are no lithologic details assigned to this well.

Driller Certification

All work performed and reported in this well log is in compliance with the Montana well construction standards. This report is true to the best of my knowledge.

Name:

Company:

License No: -

Date Completed: 1/1/1951

BEFORE THE BOARD OF OIL AND GAS CONSERVATION OF THE STATE OF MONTANA

In the Matter of the application of)	NOTICE OF
4)	INTENTION TO APPLY
Denbury Onshore, LLC)	FOR A CLASS II INJECTION
5 (2))	WELL PERMIT
for a Permit to Convert an Existing Well to Water Injection Use.)	

1. Name and address of Applicant:

Denbury Onshore, LLC 5320 Legacy Drive Plano, TX 75024

2. Legal Description including County and Approximate Footages of Surface Location of Proposed Oil and Gas Well: (and projected bottom-hole location, if a directional or horizontal well)

S&H Rentals 23X-08 Location: NESW, 1606' FSL & 2160' FWL, Sec. 8, T14N-R55E Dawson County, MT.

3. Source of fluids to be injected:

Produced Water from Denbury Onshore, LLC Operations located in the Glendive Field.

4. Zone or formation, including depth, into which fluid will be injected.

Mission Canyon-Lodgpole Formation at approximately 7134'-7748'.

5. Statement that an Aguifer Exemption will or will not be requested.

An Aquifer Exemption is not required.

Notice is hereby given that an application for a Class II injection Well Permit at the surface location set forth above will be filed with the Montana Board of Oil and Gas Conservation. Pursuant to Rules 36.22.1409, Administrative Rules of Montana, a public hearing will be held regarding said application. The hearing will be held at the Board of Oil & Gas in the Conservation Hearing Room, Billings, Montana on **Thursday, February 15, 2018**. An interested party may demand opportunity to be heard by the Montana Board of Oil and Gas Conservation concerning said application.

Montana Board of Oil and Gas Conservation

2535 St. Johns Avenue Billings MT 59102 Office: (406) 656-0040

Fax: (406) 655-6015

Naomi Johnson

From:

Lynn Hencley <Lynn.Hencley@helenair.com>

Sent:

Thursday, January 04, 2018 9:57 AM

To:

Naomi Johnson

Subject:

[EXT] RE: Public Notice for Publication - S&H Rentals 23X-08

BEFORE THE BOARD OF OIL AND GAS CONSERVATION OF THE STATE OF MONTANA NOTICE OF INTENTION TO APPLY FOR A CLASS II INJECTION WELL PERMIT

In the Matter of the application of

DENBURY ONHORE, LLC for a Permit to Convert an Existing Well to Water Injection Use.

Name and address of applicant:

Denbury Onshore, LLC

5320 Legacy Drive Plano, TX 75024

Legal Description including County and Approximate Footages of Surface Location of Proposed Oil and Gas Well: (and projected bottom-hole location, if a directional or horizontal well)
 S&H Rentals 23X-08 Location: NESW, 1606' FSL & 2160' FWL, Sec. 8, T14N-R55E Dawson County, MT.

3. Source of fluids to be injected:

4. Zone or formation, including depth, into which produced water will be injected.

Mission Canyon-Lodgpole Formation at approximately 7134'-7748'.

5. Statement that an Aquifer Exemption will or will not be

requested.

An Aquifer Exemption is not required.

Notice is hereby given that an application for a Class II Injection Well Permit at the surface location set forth above will be filed with the Montana Board of Oil and Gas Conservation. Pursuant to Rules 36.22.1409, Administrative Rules of Montana, a public hearing will be held regarding said application. The hearing will be held at the Board of Oil & Gas in the Conservation Hearing Room, Billings, Montana on Thursday, February 15, 2018. An interested party may demand opportunity to be heard by the Montana Board of Oil and Gas Conservation concerning said application.

Montana Board of Oil and Gas Conservation

2535 St. Johns Avenue Billings MT 59102 Office: (406) 656-0040 Fax: (406) 655-6015 January 5, 2018

MNAXLP

\$148.42

Lynn Hencley

Classified Recruitment Rep/Legal Adv.

Independent Record | 2222 Washington St. | P.O. Box 4249 | Helena, MT 59604 406-447-4069 lynn.hencley@helenair.com



From: Naomi Johnson [mailto:naomi.johnson@denbury.com]

Sent: Tuesday, January 02, 2018 12:43 PM

To: Hel IR Legal Ads

Subject: Public Notice for Publication - S&H Rentals 23X-08

Good Afternoon,

Please have the attached Public Notice published as soon as possible. I've attached a pdf as well as an excel format. Also please let me know how you would like payment, whether it be a check or if you accept credit card and I will get that processed for you. Please let me know if you have any questions or if anything else is needed before this can be published.

Thank you so much!

Naomi Johnson

Regulatory Compliance Specialist | North Region

Denbury Resources Inc | 5320 Legacy Dr | Plano, TX 75024 Phone: 972-673-2552 | Email: naomi.johnson@denbury.com



BEFORE THE BOARD OF OIL AND GAS CONSERVATION OF THE STATE OF MONTANA

In the Matter of the application of)	NOTICE OF
)	INTENTION TO APPLY
Denbury Onshore, LLC)	FOR A CLASS II INJECTION
)	WELL PERMIT
for a Permit to Convert an Existing Well to Water Injection Use.)	

1. Name and address of Applicant:

Denbury Onshore, LLC 5320 Legacy Drive Plano, TX 75024

2. Legal Description including County and Approximate Footages of Surface Location of Proposed Oil and Gas Well: (and projected bottom-hole location, if a directional or horizontal well)

S&H Rentals 23X-08 Location: NESW, 1606' FSL & 2160' FWL, Sec. 8, T14N-R55E Dawson County, MT

3. Source of fluids to be injected:

Produced Water from Denbury Onshore, LLC Operations located in the Glendive Field.

4. Zone or formation, including depth, into which fluid will be injected.

Mission Canyon-Lodgpole Formation at approximately 7134'-7748'.

5. Statement that an Aquifer Exemption will or will not be requested.

An Aquifer Exemption is not required.

Notice is hereby given that an application for a Class II injection Well Permit at the surface location set forth above will be filed with the Montana Board of Oil and Gas Conservation. Pursuant to Rules 36.22.1409, Administrative Rules of Montana, a public hearing will be held regarding said application. The hearing will be held at the Board of Oil & Gas in the Conservation Hearing Room, Billings, Montana on **Thursday, February 15, 2018**. An interested party may demand opportunity to be heard by the Montana Board of Oil and Gas Conservation concerning said application.

Montana Board of Oil and Gas Conservation

2535 St. Johns Avenue Billings MT 59102 Office: (406) 656-0040

Fax: (406) 655-6015

Naomi Johnson

From:

Elizabeth Kaiser < rrcomp@rangerreview.com>

Sent:

Wednesday, January 03, 2018 11:19 AM

To:

Naomi Johnson

Subject:

[EXT] Re: Public Notice for Publication - S&H Rentals 23X-08

Naomi,

I have this scheduled to publish in the 1/4/2018 issue of the Ranger-Review. The cost is \$32 and we would be happy to take a card by phone. Just ask for the office manager.

Happy New year!

Elizabeth

On Jan 3, 2018, at 8:09 AM, Naomi Johnson <naomi.johnson@denbury.com> wrote:

Good Morning!

I just wanted to make sure you received the attached Public Notice yesterday and see if there was any way this could get published in your paper this week. Please let me know!

Thanks so much, Naomi

From: Naomi Johnson

Sent: Tuesday, January 02, 2018 1:43 PM

To: 'rrcomp@rangerreview.com' <rrcomp@rangerreview.com>
Subject: Public Notice for Publication - S&H Rentals 23X-08

Good Afternoon,

Please have the attached Public Notice published as soon as possible. I've attached a pdf as well as an excel format. Also please let me know how you would like payment, whether it be a check or if you accept credit card and I will get that processed for you. Please let me know if you have any questions or if anything else is needed before this can be published.

Thank you so much!

Naomi Johnson

Regulatory Compliance Specialist | North Region

Denbury Resources Inc | 5320 Legacy Dr | Plano, TX 75024 Phone: 972-673-2552 | Email: naomi.johnson@denbury.com naomi.johnson.com <a hr

<S&H Rentals 23X-08 Public Notice.xls><S&H Rentals 23X-08 - Public Notice - Glendive Ranger Review.pdf>

Elizabeth Kaiser rrcomp@rangerreview.com 406-377-3303

SATHE ANA TICAL LABORA DRY, INC.

301 W. 2ND STREET

P.O.BOX 1527 WILLISTON. ND. 58801

701-572-3632

WATER ANALYSIS REPORT

OPERATOR: ENCORE OPERATING L.P.

DATE:

12/11/09

WELL NO.

NORTH PINE 24-19CH

LAB NO.:

W-09-3402

FIELD:

North Pine

FORMATION:

Mission Canyon

COUNTY:

Wibaux

INTERVAL:

7611'-7748'

STATE:

MT

DST #:

LOC:

not listed

SAMPLE 44 BBLS 12/21/09 PRODUCED H20

CATIONS	MG/L	MEQ/L	ANIONS	MG/L	MEQ/L
SODIUM CALCIUM MAGNESIUM IRON POTASSIUM BARIUM CHROMIUM	11950.0 1074.2 229.0 0.1 329.0 0.0	519.8 53.6 18.8 0.0 8.4 0.0	CHLORIDE CARBONATE BICARBONATE SULFATE NITRATE	20020.7 0.0 329.5 2137.8 0.0	564.8 0.0 5.4 44.5 0.0

SPECIFIC GRAVITY @ 77°F

1.020 PH

6.70

RESISTIVITY @ 77°F.ohm-meters


0.254 NACL (Calc.)

33013.7

TOTAL DISSOLVED SOLIDS (Calc.) MG/L 36070.3 HYDROGEN SULFIDE

NEG

WATER ANALYSIS PATTERN - MEG/L



REMARKS - Received 12/9/09.

DISTRIBUTION OF RESULTS Art DeGrand -- Baker MT.



Nalco Analytical Resources 1601 West Diehl Road, Naperville, Illinois 60563-1198 Phone: (630) 305-2315, Fax: (630) 305-2946, Analytical.Lab.Naperville@Nalco.com



Encore Operating LP Broadus MT USA NW1054645 31-Jan-2010 10-Feb-2010 17-Feb-2010 Sample Number: Date Sampled: Date Received: Sample Marked: West Glendive 26 SWD SAP SoldTo Number: 0001082193 Date Completed:

Water Analysis Report

Cations/Metals Total Aluminum (Al) < 1.4 mg/L Barium (Ba) 1.5 mg/L Boron (B) 120 mg/L Cadmium (Cd) < 0.14 mg/L Calcium (Ca) 3300 mg/L Chromium (Cr) < 0.43 mg/L Copper (Cu) < 0.87 mg/L Iron (Fe) 75 mg/L Lead (Pb) 2.9 mg/L Lead (Pb) 2.9 mg/L Magnesium (Mg) 430 mg/L Magnesium (Mg) 430 mg/L Manganesse (Mn) 0.24 mg/L Molybdenum (Mo) < 0.9 mg/L Nickel (Ni) < 0.9 mg/L Nickel (Ni) 1300 mg/L Silica (SiO2) 140 mg/L Solium (Na) 25000 mg/L Solium (Na) 25000 mg/L Strontium (Sr) 140 mg/L Vanadium (V) < 0.29 mg/L	0.1.07.1		Lange of	
Barium (Ba) 1.5 mg/L Boron (B) 120 mg/L Cadmium (Cd)				#
Boron (B)	Taring Committee	0000 = 02 E 34		-
Cadmium (Cd) <0.14	Year Mark Control of Control of	a capposa a spira	1000	- 6
Calcium (Ca) 3300 mg/L Chromium (Cr) 0.43 mg/L Copper (Cu) 0.87 mg/L Iron (Fe) 75 mg/L Lead (Pb) 2.9 mg/L Lithium (Li) 24 mg/L Magnesium (Mg) 430 mg/L Manganese (Mn) 0.24 mg/L Molybdenum (Mo) <0.9	77 20 20 20 20 20	et tiet ter en en en ter e	1 - 4	
Chromium (Cr) -0.43 mg/L Copper (Cu) -0.87 mg/L Iron (Fe) 75 mg/L Lead (Pb) -2.9 mg/L Lithium (Li) 24 mg/L Magnesium (Mg) 430 mg/L Manganese (Mn) 0.24 mg/L Molybdenum (Mo) -0.9 mg/L Nickel (Ni) -0.29 mg/L Potassium (K) 1300 mg/L Silica (SiO2) 140 mg/L Sodium (Na) 25000 mg/L Strontium (Sr) 140 mg/L Vanadium (V) -0.29 mg/L Zinc (Zn) -0.14 mg/L Calcium (CaCO3) 8400 mg/L Magnesium (CaCO3) 8400 mg/L Magnesium (CaCO3) 54000 mg/L Alons Senidae (Br) <200.0 mg/L	man to the second of the secon		V335480 1	11 1 W 15-17
Copper (Cu) 40.87 mg/L Iron (Fe) 75 mg/L Lead (Pb) 4.9 mg/L Lithium (Li) 24 mg/L Magnesium (Mg) 430 mg/L Manganese (Mn) 0.24 mg/L Molybdenum (Mo) <0.9	4 7 4	STATE OF THE STATE OF	1.1.00	mg/L
Iron (Fe) 75 mg/L	with the	Down to	<0.43	mg/L
Lead (Pb) 2.9 mg/L Lithium (Li) 24 mg/L Magnesium (Mg) 430 mg/L Manganese (Mn) 0.24 mg/L Molybdenum (Mo) <0.9	Copper (Cu)	5 '8 NW NS 5' 00	<0.87	mg/L
Lithium (Li) 24 mg/L Magnesium (Mg) 430 mg/L Manganese (Mn) 0.24 mg/L Molybdenum (Mo) <0.9 mg/L Nickel (Ni) <0.29 mg/L Potassium (K) 1300 mg/L Silica (SiO2) 140 mg/L Sodium (Na) 25000 mg/L Strontium (Sr) 140 mg/L Vanadium (V) <0.29 mg/L Zinc (Zn) <0.14 mg/L Calcium (CaCO3) 8400 mg/L Magnesium (CaCO3) 1800 mg/L Sodium (CaCO3) 1800 mg/L Anions Bromide (Br) <200.0 mg/L Chloride (Cl) 54000 mg/L Nitrate (NO3) <200.0 mg/L Nitrate (NO3) <200.0 mg/L Nitrate (SO4) 890 mg/L Chloride (CaCO3) 890 mg/L Sulfate (SO4) 890 mg/L Sulfate (CaCO3) 76000 mg/L Nitrate (CaCO3) 390 mg/L Chloride (CaCO3) 390 mg/L Chloride (CaCO3) 390 mg/L Nitrate (CaCO3) 390 mg/L Sulfate (CaCO3) 390 mg/L Nitrate (CaCO3) 390 mg/L	Iron (Fe)	ar a la vant	75	mg/L
Magnesium (Mg) 430 mg/L Manganese (Mn) 0.24 mg/L Molybdenum (Mo) <0.9	Lead (Pb)		<2.9	mg/L
Manganese (Mn) 0.24 mg/L Molybdenum (Mo) <0.9	Lithium (Li)	2 0.55000	24	mg/L
Molybdenum (Mo) <0.9 mg/L Nickel (Ni) <0.29	Magnesium (Mg)	101 110941 10 12 127 441	430	mg/L
Nickel (Ni) <0.29	Manganese (Mn)	1250 5 (1250 5 C)*	0.24	mg/L
Nickel (Ni) <0.29	Molybdenum (Mo)	THE TOTAL THE STATE OF THE STAT	<0.9	mg/L
Potassium (K) 1300 mg/L Silica (SiO2) 140 mg/L Sodium (Na) 25000 mg/L Strontium (Sr) 140 mg/L Vanadium (V) <0.29	Nickel (Ni)	CIRC H CONCRETE S	< 0.29	_
Silica (SiO2) 140 mg/L Sodium (Na) 25000 mg/L Strontium (Sr) 140 mg/L Vanadium (V) <0.29	Potassium (K)	80.00		C1114c3-6
Sodium (Na) 25000 mg/L Strontium (Sr) 140 mg/L Vanadium (V) <0.29	Process of the contract of the	THE PERSON NAMED IN COLUMN	10 Table 10	Misch W.
Strontium (Sr) 140 mg/L Vanadium (V) <0.29	AND THE PERSON NAMED IN	5255 ff(f) Police 15	Tar. 10 10 10 10 10 10 10 10 10 10 10 10 10	Mark W
Vanadium (V) <0.29	and the second s			
Zinc (Zn) <0.14	0.00000	ex exem N o	45.0	-
Calcitum (CaCO3) 8400 mg/L Magnesium (CaCO3) 1800 mg/L Sodium (CaCO3) 54000 mg/L Calculated Hardness (CaCO3) 10000 mg/L Anions Sample 200.0 mg/L Bromide (Br) 200.0 mg/L 200.0 mg/L Chloride (CI) 54000 mg/L 34000 mg/L Nitrate (NO3) 200.0 mg/L 320.0 mg/L Sulfate (SO4) 890 mg/L 200.0 mg/L Chloride (CaCO3) 76000 mg/L Nitrate (CaCO3) 200.0 mg/L Nitrate (CaCO3) 200.0 mg/L ALK - Alkalinity 320 mg/L Bicarbonate (CaCO3) 160 mg/L Methyl Orange (CaCO3) 160 mg/L		320 to 330 feet		14 040
Magnesium (CaCO3) 1800 mg/L Sodium (CaCO3) 54000 mg/L Calculated Hardness (CaCO3) 10000 mg/L Anions Bromide (Br) <200.0 mg/L	1 1	and the Second I has	1 10 10 N 10 TO 10	AATT A AT
Sodium (CaCO3) 54000 mg/L Calculated Hardness (CaCO3) 10000 mg/L Anions Sample (Br) 200.0 mg/L Chloride (CI) 54000 mg/L Nitrate (NO3) 200.0 mg/L Nitrite (NO2) 200.0 mg/L Sulfate (SO4) 890 mg/L Chloride (CaCO3) 76000 mg/L Nitrate (CaCO3) <160 mg/L		200 000 ENE	98 [4 9 9 9	
Calculated Hardness (CaCO3) 10000 mg/L Anions Seromide (Br) <200.0 mg/L Chloride (Cl) 54000 mg/L Nitrate (NO3) <200.0 mg/L		E 75 5 1 15	12 (CA) (CA) (CA)	
Anions Bromide (Br)	to the Color to the	CO2)		10 F 400 11
Bromide (Br)	Culculated Haraness (Ca	50,5 % 50 100	10000	mg/L
Bromide (Br)	Anions			
Chloride (Cl) 54000 mg/L Nitrate (NO3) <200.0 mg/L Nitrite (NO2) <200.0 mg/L Sulfate (SO4) 890 mg/L Chloride (CaCO3) 76000 mg/L Nitrate (CaCO3) 76000 mg/L Sulfate (CaCO3) 920 mg/L ALK - Alkalinity Bicarbonate (CaCO3) 160 mg/L Methyl Orange (CaCO3) 160 mg/L				<200.0 mg/l
Nitrate (NO3) <200.0 mg/L		AC-90 Self- no. 5 252		
Nitrite (NO2) <200.0 mg/L	111	3 S U S U S S	1. 10/71 700 51	
Sulfate (SO4) 890 mg/L Chloride (CaCO3) 76000 mg/L Nitrate (CaCO3) <160 mg/L		e		
Chloride (CaCO3) 76000 mg/L Nitrate (CaCO3) <160 mg/L	7 11111			
Nitrate (CaCO3) <160 mg/L		119		
Sulfate (CaCO3) 920 mg/L ALK - Alkalinity Bicarbonate (CaCO3) 160 mg/L Methyl Orange (CaCO3) 160 mg/L	60 H A O	98 98 W 100 9	190	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
ALK - Alkalinity Bicarbonate (CaCO3) 160 mg/L Methyl Orange (CaCO3) 160 mg/L		ne v v sjære	9.9	
Bicarbonate (CaCO3) 160 mg/L Methyl Orange (CaCO3) 160 mg/L	12.21 6.3	POST (0.00 E)	H 7000 F	920 mg/L
Methyl Orange (CaCO3) 160 mg/L	-			
The second secon		1 - 100 200 200	w. 17.900 m	160 mg/L
Phenolphthalein (CaCO3) <10 mg/L		(4040) (41 × 1)	6.588 as	160 mg/L
	Phenolphthalein (CaCO3)			<10 mg/L

Authorized by : Jessica Rubino







Nalco Analytical Resources

1601 West Diehl Road, Naperville, Illinois 60563-1198 Phone: (630) 305-2315, Fax: (630) 305-2946, Analytical.Lab.Naperville@Nalco.com



Encore Operating LP Broadus MT USA Sample Marked: West Glendive 26 SWD SAP SoldTo Number: 0001082193 Sample Number: Date Sampled: Date Received: NW1054645 31-Jan-2010 10-Feb-2010 17-Feb-2010 Date Completed:

Water Analysis Report

Others Conductivity 110000 μS/cm 6.9 pH Units

Authorized by : Jessica Rubino

Natco Analytical Resources - Naperville An ISO 9001:2000 Cerified Laboratory DNV Cert. #: CERT-1061G-2005-AQ-HOU-ANAB

PLACE STICKER AT TOP OF ENVELOPE TO THE RIGHT OF THE NETURN ADDRESS. FOLD AT DOTTED LINE

CERTIFIED MAIL



January 4, 2018

Trangmoe Land LLP 115 Cooke St. Glendive, MT 59330-2016

RE:

Glendive Field

S&H Rentals 23X-08 Section 8, T14N-R55E Dawson County, MT

Dear Surface Land Owner,

Within the Glendive Field, Denbury Onshore, LLC plans to convert the S&H Rentals 23X-08 to a Salt Water Disposal well.

In accordance with the rules and regulations of the Montana Board of Oil and Gas Conservation (MBOGC)—administered Underground Injection Control (UIC) in Montana, Denbury is required to give notice to each owner of land within one-quarter mile radius of the well site, that we have applied for a permit to perform this work.

Therefore, as a landowner within the prescribed radius, we are hereby informing you that we have applied to the MBOGC for a permit to convert the subject well to salt water disposal. You may comment on the application at any time by mail or phone before the hearing, or be present at the hearing. The hearing will be held on Thursday February 15, 2018 at the Board of Oil & Gas in the Conservation Hearing Room. It is located at 2535 St. Johns Avenue, Billings, Montana 59102.

For further information, contact Naomi Johnson at (972) 673-2552 or George Hudak of the MBOGC at (406) 656-0040.

Sincerely,

Naomi Johnson

Regulatory Compliance Specialist

Massiff MML

Denbury Onshore, LLC

PLACE STICKER AT TOP OF ENVELOPE TO THE RIGHT OF THE RETURN ADDRESS. FOLD AT DOTTED LINE

CERTIFIED MAIL



January 4, 2018

7032 7416

9991

Dale Schendel Wendi L. Trustees 6038 Glass Dr. Helena, MT 59602-6454

RE:

Glendive Field

S&H Rentals 23X-08 Section 8, T14N-R55E Dawson County, MT

Dear Surface Land Owner,

Within the Glendive Field, Denbury Onshore, LLC plans to convert the S&H Rentals 23X-08 to a Salt Water Disposal well.

In accordance with the rules and regulations of the Montana Board of Oil and Gas Conservation (MBOGC)—administered Underground Injection Control (UIC) in Montana, Denbury is required to give notice to each owner of land within one-quarter mile radius of the well site, that we have applied for a permit to perform this work.

Therefore, as a landowner within the prescribed radius, we are hereby informing you that we have applied to the MBOGC for a permit to convert the subject well to salt water disposal. You may comment on the application at any time by mail or phone before the hearing, or be present at the hearing. The hearing will be held on Thursday February 15, 2018 at the Board of Oil & Gas in the Conservation Hearing Room. It is located at 2535 St. Johns Avenue, Billings, Montana 59102.

For further information, contact Naomi Johnson at (972) 673-2552 or George Hudak of the MBOGC at (406) 656-0040.

Sincerely,

Naomi Johnson

Regulatory Compliance Specialist

Call JUML

Denbury Onshore, LLC